



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Version number 3

Revision: 23.07.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Lightdon Bonding**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Dental bonding material
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Dreve Dentamid GmbH
Max-Planck-Straße 31
59423 Unna / Germany
Tel.: ++49 2303 / 8807-0
Fax.: ++49 2303 / 8807-55
- **Further information obtainable from:**
Department Research & Development
Fax: ++49 2303 / 8807-562
Email: sicherheitsdatenblatt@dreve.de
- **1.4 Emergency telephone number:**
Tel.: ++ 49 211 / 797-3350
Plant Fire Department Henkel

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H335 May cause respiratory irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
methyl methacrylate
2-Propenoic acid, reaction products with dipentaerythritol

(Contd. on page 2)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Version number 3

Revision: 23.07.2015

Trade name: Lightdon Bonding

(Contd. of page 1)

- **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**

- **Description:** Light-curing adhesive on the basis of methacrylate

- **Dangerous components:**

CAS: 80-62-6 EINECS: 201-297-1	methyl methacrylate ⚠ Flam. Liq. 2, H225; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	50-100%
CAS: 1384855-91-7	2-Propenoic acid, reaction products with dipentaerythritol ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	10-25%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- **After eye contact:**

Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing:**

Do not induce vomiting.

Call for a doctor immediately.

- **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 3)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Version number 3

Revision: 23.07.2015

Trade name: Lightdon Bonding

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fire with alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:**
Water
Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Avoid contact with skin and eyes.
Do not breathe vapour/spray.
Keep away from ignition sources.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store at max. 25 °C.
Protect from heat and direct sunlight.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Version number 3

Revision: 23.07.2015

Trade name: **Lightdon Bonding**

(Contd. of page 3)

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

80-62-6 methyl methacrylate	
WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

- **Respiratory protection:**

Not necessary if room is well-ventilated.
Use suitable respiratory protective device in case of insufficient ventilation.
Filter AX

- **Protection of hands:**



Protective gloves

Protective gloves should be changed regularly, especially after intensive contact with the product. For every workplace a suitable type of protective gloves must be selected. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**

Butyl rubber (0,7 mm) EN 374

As there are many different conditions in every day work these indications can only serve as an aid to orientation for the selection of suitable gloves for the handling of chemical products. By no means they can replace qualifying examinations by the end-user.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

(Contd. on page 5)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Version number 3

Revision: 23.07.2015

Trade name: **Lightdon Bonding**

(Contd. of page 4)

· **Eye protection:**

Tightly sealed goggles

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form: Fluid
Colour: Colourless

· **Odour:** Ester-like· **Odour threshold:** Not determined.· **pH-value:** Not determined.· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 101 °C

· **Flash point:** 10 °C· **Flammability (solid, gaseous):** Not applicable.· **Ignition temperature:** 430 °C· **Decomposition temperature:** Not determined.· **Self-igniting:** Product is not selfigniting.· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.· **Explosion limits:**

Lower: 2.1 Vol %

Upper: 12.5 Vol %

· **Oxidising properties** Not determined· **Vapour pressure at 20 °C:** 47 hPa· **Density:** Not determined.· **Relative density** Not determined.· **Vapour density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**

Dynamic: Not determined.

Kinematic: Not determined.

· **Solvent content:**

Organic solvents: 0.0 %

(Contd. on page 6)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Version number 3

Revision: 23.07.2015

Trade name: Lightdon Bonding

(Contd. of page 5)

- | | |
|--------------------------------|--|
| · 9.2 Other information | No further relevant information available. |
|--------------------------------|--|

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No dangerous reactions if used according to specifications.
- **10.2 Chemical stability** Stable if used according to specifications.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
Protect from heat and direct sunlight.
- **10.3 Possibility of hazardous reactions** Exothermic polymerisation.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**
In the presence of peroxides and other radical forming substances, reducing agents and/or heavy metal ions,
exothermic polymerisation is possible.
- **10.6 Hazardous decomposition products:** Irritant vapours for the eyes (MMA).

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
- **LD/LC50 values relevant for classification:**
Methylmethacrylate: LD-50 oral >5000 mg/kg rat (Lit.)
LD-50 inhalativ 7093 ppm/4h rat (Lit.)
- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation** Sensitisation possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
Fish Toxicity (MMA):
LC-50 > 79 mg/l OECD 203
NOEC: 40 mg/l ISO 7346
Exposure: 96 h EEC84
Spezies: 449 V, C1
Oncorhynchus mykiss
Bacterial Toxicity: ECO: 100 mg/l
Spezies of cells: Pseudomonas putida
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 7)

GB



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Version number 3

Revision: 23.07.2015

Trade name: **Lightdon Bonding**


(Contd. of page 6)

- **Additional ecological information:**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.
- **European waste catalogue** 070208
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Alcohol

SECTION 14: Transport information

<ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA 	UN1247
<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG, IATA 	1247 METHYLMETHACRYLAT, MONOMER, STABILISIERT, GEMISCH METHYL METHACRYLATE MONOMER, STABILIZED, MIXTURE
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG, IATA 	<div style="text-align: center;">  </div> <ul style="list-style-type: none"> · Class · Label
<ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids. 3
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	II
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: 	No
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: 	Warning: Flammable liquids. 339 F-E,S-D
<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	Not applicable.

(Contd. on page 8)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Version number 3

Revision: 23.07.2015

Trade name: Lightdon Bonding

(Contd. of page 7)

· Transport/Additional information:
· ADR
· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500

ml

· Transport category

2

· Tunnel restriction code

D/E

· IMDG
· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500

ml

· UN "Model Regulation":
UN1247, METHYL METHACRYLATE
MONOMER, STABILIZED, 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
· Directive 2012/18/EU
· Named dangerous substances - ANNEX I None of the ingredients is listed.

· National regulations:
· Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

· Department issuing MSDS: Department Research & Development

· Contact: Dr. Thomas Veit, Lothar Sutor

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 9)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.07.2015

Version number 3

Revision: 23.07.2015

Trade name: Lightdon Bonding

(Contd. of page 8)

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

GB