

CATTANI IMUMOOTTORIT



04951

UNI JET 75 - 1 HOITOHUONE

- Max Vacuum for continuous operation = 130 mBar
- H = 251 mm, W = 232 mm, D = 246 mm
- Single phase - 3.1 A - 0.42 kW
- 62 dB(A)
- 1250 l/min



04954

TECNO JET -2 HOITOHUONETTA

- Max Vacuum for continuous operation = 140 mBar
- H = 320 mm, W = 303 mm, D = 302 mm
- Single phase - 5.5 A - 0.75 kW
- 64 dB(A)
- 2000 l/min



83983

TECNO JET 2V - (3-PHASE) 2 HOITOHUONETTA

- Max Vacuum for continuous operation = 235 mBar
- H = 320 mm, W = 303 mm, D = 302 mm
- 3 phase - 7.5 A - 3.4/1.95 kW
- 65 dB(A)
- 2000 l/min



04953

FLUX JET 2V (3-PHASE ONLY) - 4 HOITOHUONETTA

- Max Vacuum for continuous operation = 230 mBar
- H = 341 mm, W = 334mm, D = 405mm
- 3 phase - 6.4/3.7 A - 1.5kW
- 72 dB(A)
- 3300 l/min



81513

MEDIO JET (3-PHASE ONLY) - 7 HOITOHUONETTA

- Max Vacuum for continuous operation = 175 mBar
- H = 420 mm, W = 400 mm, D = 335 mm
- 3 phase - 9/5.2 A - 2.2 kW
- 76 dB(A)
- 5000 l/min

HAMMASVÄLINE