

Hygopac – Peace of mind is the best package

Sealing device for transparent sterile packaging

Trust in our quality. Hygopac – Tried and tested in packaging processes within dental surgeries.



Optimal feed-in of sterile goods packaging



Hygopac sealing device

Overview of Hygopac

- Optimal pressing pressure for consistent seam quality
- Conveyor belt principle is quick and efficient
- Stepless temperature adjustment for optimal seal seam
- Significant time saving compared to bar-sealing devices
- Long service life thanks to compact and sturdy build
- Economical base version



Hygopac

Sealing device for transparent sterile packaging



Hygopac Plus

Verifiable Sealing device in accordance with DIN EN ISO 11607-2



	Hygopac	Hygopac Plus
Technical data		
Voltage	230 V	230 V
Electrical frequency	50 – 60 Hz	50 – 60 Hz
Power output	550 W	550 W
Heating performance	2 × 250 W	2 × 250 W
Warm-up time	approx. 3 min	approx. 3 min
Sealing temperature	to 240 °C	to 220 °C
Temperature adjustment	stepless	exact in 5 °C increments
Sealing speed	5.3 m/min	10 m/min
Seal-seam width	9 mm	12 mm
Weight	7.2 kg	7.2 kg
Dimensions (H × W × D)	160 × 435 × 135 mm	170 × 370 × 140 mm
Time saved in comparison to bar-sealing devices	●	●
Control panel with display		●
Validation		
Process control (sealing temperature, sealing speed, pressing pressure)		●
Function assessment	●	●
Manufacturer performance assessment	●	●
Storage of important parameters		●
Automatic data storage via SD card or network		●
Optional accessories		
Instrument table	●	●
Roll cutting mechanism	●	●